

(2) If an applicant plans to operate a launch site located on a federal launch range, and if the applicant is required by the federal launch range to comply with the federal launch range's explosive safety requirements, the applicant shall submit the explosive site plan submitted to the federal launch range.

(e) *Launch site operations.* An applicant shall provide the information necessary to demonstrate compliance with the requirements of §§ 420.53, 420.55, 420.57, 420.59, 420.61, and 420.71.

**§ 420.17 Bases for issuance of a license.**

(a) The FAA will issue a license under this part when the FAA determines that:

(1) The application provides the information required by § 420.15;

(2) The FAA has completed an analysis of the environmental impacts associated with the proposed operation of the launch site, in accordance with NEPA, 40 CFR parts 1500-1508, and FAA Order 1050.1D;

(3) The launch site location meets the requirements of §§ 420.19, 420.21, 420.23, 420.25, 420.27, and 420.29;

(4) The applicant has completed the agreements required by § 420.31;

(5) The application demonstrates that the applicant shall satisfy the requirements of §§ 420.53, 420.55, 420.57, 420.59, 420.61 and 420.71;

(6) The explosive site plan meets the criteria of §§ 420.63, 420.65, 420.67 and 420.69; and

(7) Issuing a license would not jeopardize foreign policy or national security interests of the United States.

(b) The FAA advises an applicant, in writing, of any issue arising during an application review that would lead to denial. The applicant may respond in

writing, submit additional information, or amend its license application.

**§ 420.19 Launch site location review—general.**

(a) To gain approval for a launch site location, an applicant shall demonstrate that for each launch point proposed for the launch site, at least one type of expendable or reusable launch vehicle can be flown from the launch point safely. For purposes of the launch site location review:

(1) A safe launch must possess a risk level estimated, in accordance with the requirements of this part, not to exceed an expected average number of 0.00003 casualties ( $E_c$ ) to the collective member of the public exposed to hazards from the flight ( $E_c \leq 30 \times 10^{-6}$ ).

(2) Types of launch vehicles include orbital expendable launch vehicles, guided sub-orbital expendable launch vehicles, unguided sub-orbital expendable launch vehicles, and reusable launch vehicles. Orbital expendable launch vehicles are further classified by weight class, based on the weight of payload the launch vehicle can place in a 100-nm orbit, as defined in table 1.

(b) If an applicant proposes to have more than one type of launch vehicle flown from a launch point, the applicant shall demonstrate that each type of expendable or reusable launch vehicle planned to be flown from the launch point can be flown from the launch point safely.

(c) If an applicant proposes to have more than one weight class of orbital expendable launch vehicles flown from a launch point, the applicant shall demonstrate that the heaviest weight class planned to be flown from the launch point can be flown from the launch point safely.

TABLE 1 OF § 420.19—ORBITAL EXPENDABLE LAUNCH VEHICLE CLASSES BY PAYLOAD WEIGHT (LBS)

100 nm orbit	Weight class			
	Small	Medium	Medium large	Large
28 degrees inclination * .....	≤4400	>4400 to ≤11100	>11100 to ≤18500	>18500
90 degrees inclination .....	≤3300	>3300 to ≤8400	>8400 to ≤15000	>15000

\* 28 degrees inclination orbit from a launch point at 28 degrees latitude.